


P6103W-V3

NEW

10.1" WXGA TFT Widescreen Industrial LCD Monitor

Features

- 10.1" WXGA TFT LED backlight LCD
- Projected capacitive multi-touch
- NEMA 4/12 (IP65) compliant flat panel monitor
- Supports panel mount, wall mount, and VESA arm
- Full range screw-type (locked) AC-in
- DP, VGA, and HDMI with multi-signal inputs



Introduction

The P6103W-V3 is an ultra slim industrial LCD monitor, which adopts 10.1-inch 350 nits WXGA LED backlight LCD display and supports multi-signal interfaces including DisplayPort, VGA, and HDMI. It features NEMA 4/12 and IP65 compliant front bezel, screw-type adaptor plug design. Moreover, the P6103W-V3 supports panel mount, wall mount or VESA FPMPMI (Video Electronics Standards Association Flat Panel Monitor Physical Mounting Interface) mounting. With the compact mechanism design, users can enjoy free from space constraint. It is especially suitable for POI/POS, excellent HMI, and all kinds of heavy-duty industrial fields.

Specifications

Front Bezel	NEMA 4/12 (IP65)-compliant and metal front bezel
Mounting	Panel mount, wall mount or VESA arm FPMPMI mounting (video electronics standards association flat panel monitor physical mounting interface)
LCD Panel	Display 10.1" WXGA TFT LCD Max. Resolution 1280 x 800 Max. Colors 16.7M Active Area (mm) 216.96 x 135.60 Pixel Pitch (mm) 0.1695 x 0.1695 Response Time 25ms Backlight LED backlight Backlight MTBF 30,000 hrs Viewing Angle (H/V) 170°/170° Contrast Ratio 800 (TYP.) Brightness (cd/m ²) 350 nits
Display Control	OSD (on screen display)
Input Signal	DisplayPort VGA HDMI Touchscreen: USB interface

Specifications

I/O Connectors	1 x USB for touchscreen version 1 x Audio (Line-in) 2 x Speaker 1 x VGA 1 x DisplayPort 1 x HDMI 1 x Power input with screw type connector
Power Adapter	AC version: 100 to 240 VAC-DC, 12V3A, 36W power adapter
Power Consumption	12W
Touchscreen	Projected capacitive touch
Dimensions	260.8 mm (10.27") (W) x 38 mm (1.5") (D) x 194.1 mm (7.64") (H)
Packing Dimensions	415 mm (16.33") (W) x 99 mm (3.9") (D) x 313 mm (12.32") (H)
Weight (net/gross)	1.036 kg (2.28 lbs)/1.6 kg(3.53 lbs)
Environment	Operating temperature: 0°C to +50°C (+32°F to +122°F) Relative humidity: 10% to 90% @ +40°C, non-condensing
Packing List	1 x P6103W-V3 unit 1 x VGA cable 1 x USB cable for touch 1 x Audio cable 1 x Adapter (AC version only)
Certificate	CE

Ordering Information

P6103WPC-AC-U-V3 (P/N: E226103105)	10.1" industrial monitor with capacitive touch screen and AC version
---------------------------------------	--

*Other configuration by request
*Specification and certifications may vary based on different requirements

Optional Accessories

590000012700	HDMI cable
59461713910E	DisplayPort cable
82251030100E	Panel mount kit
82238460050E	Wall mount kit
E226171119	Desktop stand

Dimensions

