

PWR Power Module Series

Hot-swappable power modules for Moxa switches



Features and Benefits

- -40 to 85°C wide operating temperature
- IEC 61850-3 and IEEE 1613 compliant

Certifications



Introduction

The PWR Power Module Series hot-swappable power modules are designed for Moxa switches. The power modules allow supported switches to use 24/48 VDC or 110/220 VAC/VDC.

Specifications

Power Parameters

Input Voltage	<p>PWR-HV-P48: 110/220 VDC/VAC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p> <p>PWR-HV-P48-A : 110/220 VDC/VAC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p> <p>PWR-LV-P48: 24/48 VDC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p> <p>PWR-LV-P48-A: 24/48 VDC for the switch system 48 VDC for PoE systems (53 to 57 VDC is recommended for PoE+ devices)</p> <p>PWR-HV-NP: 110/220 VDC/VAC for the switch system</p> <p>PWR-LV-NP: 24/48 VDC for the switch system</p>
Operating Voltage	<p>PWR-HV-P48: 88 to 300 VDC, 90 to 264 VAC for the switch system 46 to 57 VDC for PoE systems</p> <p>PWR-HV-P48-A : 88 to 300 VDC, 90 to 264 VAC for the switch system 46 to 57 VDC for PoE systems</p> <p>PWR-LV-P48:</p>

	<p>18 to 72 VDC for the switch system 46 to 57 VDC for PoE systems</p> <p>PWR-LV-P48-A: 18 to 72 VDC for the switch system 46 to 57 VDC for PoE systems</p> <p>PWR-HV-NP: 88 to 300 VDC, 90 to 264 VAC for the switch system</p> <p>PWR-LV-NP: 18 to 72 VDC for the switch system</p>
Reverse Polarity Protection	Supported
Alarm Contact Channels	1 relay output with current carrying capacity of 2 A @ 30 VDC or 0.5 A @ 125 VAC

Physical Characteristics

Weight	<p>PWR-HV-P48: 360 g (0.79 lb) PWR-HV-P48-A: 420 g (0.93 lb) PWR-LV-P48: 360 g (0.79 lb) PWR-LV-P48-A: 400 g (0.88 lb) PWR-HV-NP: 340 g (0.75 lb) PWR-LV-NP: 340 g (0.75 lb)</p>
--------	--

MTBF

Time	<p>PWR-HV-P48: 1,530,831 hrs PWR-HV-P48-A: 1,530,831 hrs PWR-LV-P48: 1,388,747 hrs PWR-LV-P48-A: 1,388,747 hrs PWR-HV-NP: 2,556,214 hrs PWR-LV-NP: 2,710,293 hrs</p>
Standards	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
Details	See www.moxa.com/warranty

Ordering Information

Model Name	Input Voltage	Operating Voltage	Supported Series
PWR-HV-P48	110/220 VDC/VAC 48 VDC for PoE systems	88-300 VDC, 90-264 VAC 46 to 57 VDC for PoE systems	<p>PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series</p>
PWR-HV-P48-A	110/220 VDC/VAC 48 VDC for PoE systems	88-300 VDC, 90-264 VAC 46 to 57 VDC for PoE systems	<p>MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series</p>
PWR-HV-NP	110/220 VDC/VAC	88-300 VDC, 90-264 VAC	<p>PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series</p>

Model Name	Input Voltage	Operating Voltage	Supported Series
			MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series
PWR-LV-P48	24/48 VDC 48 VDC for PoE systems	18-72 VDC 46 to 57 VDC for PoE systems	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series
PWR-LV-P48-A	24/48 VDC 48 VDC for PoE systems	18-72 VDC 46 to 57 VDC for PoE systems	MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series
PWR-LV-NP	24/48 VDC	18-72 VDC	PT-G7728 Series PT-G7828 Series MDS-G4012 Series MDS-G4020 Series MDS-G4028 Series MDS-G4012-L3 Series MDS-G4020-L3 Series MDS-G4028-L3 Series MDS-G4012-4XGS Series MDS-G4020-4XGS Series MDS-G4028-4XGS Series MDS-G4012-L3-4XGS Series MDS-G4020-L3-4XGS Series MDS-G4028-L3-4XGS Series

© Moxa Inc. All rights reserved. Updated Sep 13, 2022.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.